


## S P E C I F I C A T I O N S

1. NAME : CABLE TYPE ELECTRODE LEVEL SENSOR
2. MODEL : CE 8 8 - □  
 Body qty. : 1 ~ 6
3. MEASURING OBJECT : Clean and conductive liquid
4. ENVIRONMENT  
 4.1 Working Temperature : - 20 to 50 ℃ (Get rid of dew)
5. CONSTRUCTION : IP 45
6. MECHANICAL CHARACTERISTICS  
 6.1 Electrode Withstand Pressure : Max. 200 kPa
7. PHYSICAL
- 7.1 Mounting : Flange
- 7.2 Material
- (1) Terminal Box : Acrylonitrile-butadiene-styrene
  - (2) Flange : Polyvinyl Chloride
  - (3) Electrode Rod : Titanium
  - (5) Cable : Polyvinyl Chloride sheath
  - (6) Anchor Weight : Polyvinyl Chloride (Built-in Carbon Steel)
  - (7) Rope : Polyethylene (φ6.0)
  - (8) Cable Clip : Polyvinyl Chloride
- 7.3 Dimension
- (1) Flange : Equivalent JIS 10K 100A (Proviso 4 holes)
  - (2) Body : φ38 mm × H80 mm
  - (3) Electrode Rod : φ5.2 mm
  - (4) Cable : φ6.5 mm × 6000 mm (VCTF 0.5 mm<sup>2</sup> × 2-core)
  - (5) Anchor Weight : φ76 mm × H156 mm
- 7.4 Cable Inlet : Equivalent JIS F 20a (G 3/4)
- 7.5 Mass
- (1) Terminal Box and Flange : Approx. 1.6 kg (Except body, cable, and anchor Weight)
  - (2) Body : Approx. 0.6 kg (Including 6000 mm cable)
  - (3) Cable : Approx. 65 g/m
  - (4) Anchor Weight : Approx. 3 kg

## W A R R A N T Y

NOHKEN INC. products are warranted for a period of 1(one) year from date of original factory shipment, provided that handling, operation and maintenance of products shall be subjected to " NOHKEN's INSTRUCTION MANUAL ".