

DATE (YYYY-MM-DD)	APP. BY	CH. BY	PREP. BY
2005-10-25	T.C.	T.H.	S.B.

S P E C I F I C A T I O N S

1. NAME : ELECTRODE LEVEL SENSOR
2. MODEL : FE83C-□
└─┬─┘
└─┬─┘ Electrode qty. : 2 ~ 6
3. MEASURING OBJECT : Clean and conductive liquid
4. ENVIRONMENT
4.1 Working Temperature : -20 to 50 °C (Get rid of dew)
5. CONSTRUCTION : IP43
6. PHYSICAL
- 6.1 Mounting : Thread
- 6.2 Material
- (1) Terminal Box : PVC
 - (2) Box Cover : PVC
 - (3) Electrode Rod : NW 0276 (Equivalent Hastelloy C)
 - (4) Connector : NW 0276 (Equivalent Hastelloy C)
 - (5) Insulation Tube : Polyolefine (L. electrode rod is not covered by Insulation Tube.)
- 6.3 Dimension
- (1) Thread : G 2
 - (2) Electrode Rod : φ5.2
- 6.4 Cable Inlet : Equivalent JIS F 20a (G 3/4)
- 6.5 Mass : Approx. 0.4 kg (Except electrode rod)
- 6.6 Mass of Electrode Rod : Approx. 190 g/m

W A R R A N T Y

NOHKEN INC. products are warranted for a period of one (1) year from date of original factory shipment, provided that handling, operation and maintenance of products shall be subjected to "NOHKEN INSTRUCTION MANUAL".