

S P E C I F I C A T I O N S

1. NAME : OPTICAL TYPE INTERFACE SENSOR
2. MODEL : OX10 (Sensor)
3. MEASURING OBJECT : Deposition, Interface
4. OPERATION CHARACTERISTICS
- 4.1 Separated Length : Maximum Distance Between Sensor And Converter: 20 m
(When using two JIS 1.5D-2V high-frequency cables.)
5. MECHANICAL CHARACTERISTICS
- 5.1 Allowable Pressure : 100 kPa
6. ENVIRONMENT
- 6.1 Temperature of In Container: -10 to +70 °C
Terminal Box: -10 to +55 °C
7. CONSTRUCTION : Spray-proof construction (IP 54)
8. PHYSICAL
- 8.1 Material of In Container : 304 Stainless steel (SUS 304)
Fluoro Ethylene Propylene (FEP)
Terminal Box : Aluminium Casting (AC)
(Melamine Coating Munsell 2.5PB 3.5/10)
- 8.2 Mass : Approx. 3.2 kg
- 8.3 Flange Size : JIS 5K 65A
- 8.4 Cable Inlet : G 1/2

W A R R A N T Y

NOHKEN INC. products are warranted for a period of 1(one) year from date of original factory shipment, provided that handling, operation and maintenance of products shall be subjected to "NOHKEN's INSTRUCTION MANUAL".